



Equivalent Round (in)			A	B	C	D	E	Section Length	Lbs / Section
Dia.	Rise	Span	Wall (in)	Bell Width	Bell Depth	Spigot Width	Spigot Length		
42	34	53	5	1.875	3.5	2.50	3.5	8.0'	6456
48	38	60	5.5	2.1875	3.75	2.875	3.75	8.0'	8080
54	43	68	6	2.375	4.0	3.125	4.0	8.0'	9960
60	48	76	6.5	2.625	4.0	3.375	4.0	8.0'	11952
66	53	83	7	2.75	5.0	3.75	5.0	8.0'	14112
72	58	91	7.5	2.875	5.5	4.00	5.5	8.0'	16456
78	63	98	8	3.00	6.0	4.25	6.0	8.0'	19008
84	68	106	8.5	3.25	6.0	4.50	6.0	8.0'	21704
90	72	113	9	3.50	6.0	4.75	6.0	8.0'	24584
96	77	121	9.5	3.75	6.0	5.00	6.0	8.0'	27680
102	82	128	9.75	4.50	7.0	5.50	7.0	8.0'	29800
108	87	136	10	4.75	7.0	5.75	7.0	6.0'	24452

Elliptical Pipe Is Manufactured To ASTM C-507, Reinforcing Class As Required.

Elliptical Pipe Is Independently Air & Hydrostatic Tested.



401 Kelton St Bay City, MI 48706		36" to 108" Precast Concrete Elliptical Pipe Detail			
5281 Lansing Rd Charlotte, MI 48813		2701 Chicago Dr SW Wyoming, MI 49519			
4950 White Lake Rd Clarkston, MI 48346		3756 Centennial Rd Sylvania, OH 43560		Date 10 Aug 22	Rev. No. Revised
				Rev. No. BmG	Scale NTS
					01.03